

Product data sheet

CB flex



Carry bar for safe closing of double leaf fire protection doors

AREAS OF APPLICATION

- For use on double leaf doors with closing sequence control
- For full panic applications
- Single-action doors up to 1400 mm leaf width

**PRODUCT FEATURES**

- Ensures a minimum opening of the active leaf when opening via the passive leaf and thus activates the closing sequence control
- Variable, concealed length adjustment up to 210 mm overhang
- For flexible shortening

TECHNICAL DATA

Productname CB flex

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour
GEZE CB flex *	for use on all 2-leaf rebated doors. Concealed length adjustment with variable adjustment up to 210 mm leaf protrusion, hinged mechanism not visible, profile can be shortened if necessary, with attachment material	182652	white RAL 9016
GEZE CB flex	for use on all 2-leaf rebated doors. Concealed length adjustment with variable adjustment up to 210 mm leaf protrusion, hinged mechanism not visible, profile can be shortened if necessary, with attachment material	153602	silver-coloured
GEZE CB flex	for use on all 2-leaf rebated doors. Concealed length adjustment with variable adjustment up to 210 mm leaf protrusion, hinged mechanism not visible, profile can be shortened if necessary, with attachment material	153728	according to RAL