

# Product data sheet GEZE ActiveStop surfacemounted configured \*



Door damping on both sides for interior swing doors, configured for timber or glass doors

## AREAS OF APPLICATION

- ightarrow Right and left single-action doors for interior use
- ightarrow Room doors with high access convenience
- ightarrow Single-action doors up to 1100 mm leaf width
- ightarrow Surface-mounted installation, for retrofitting on existing doors
- ightarrow Barrier-free access in accordance with DIN 18040-2



### **PRODUCT FEATURES**

- ightarrow Door opening angle with variable adjustment from 80°-140°
- ightarrow Can be used for right and left hand doors without conversion
- ightarrow Soft opening and closing of doors up to max. 45 kg leaf weight
- ightarrow Gentle stopping, quiet closing and comfortable keeping open of doors
- ightarrow Practically eliminates slamming doors, trapped fingers, and damage to walls and furniture
- ightarrow Secure holding of the door when open, meaning no door is stopper necessary
- ightarrow Opening and closing damping when installed can be set via a valve
- ightarrow Integrated safety valve offers overload protection

#### **TECHNICAL DATA**

Productname	GEZE ActiveStop surface-mounted configured * 34 mm			
Depth				
Height	68 mm			
Leaf weight (max.)	45 kg			
Leaf width (max.)	1100 mm			
Category of door	flush-mounted, rebated			
Identical design for DIN left and DIN right	Yes			
Installation type	surface-mounted			
Adjustable draw-in damper	Yes, via valve			
Draw-in damper in direction of closing movement from	25 °			
Free swing area	25 ° - 60 °			
Draw-in damper in direction of opening movement from	60 °			
Adjustable door opening angle	Yes, stepless			
Hold-open position adjustable	80 ° - 140 °			
Safety valve againts overload	Yes			

#### **VARIANTS / ORDER INFO**

Designation	Description	ldent- No.	Colour	Dimensions	DIN direction
GEZE ActiveStop surface- mounted configured *	Door damping on both sides for interior swing doors, configured for timber or glass doors	184107	according to RAL	370 x 68 x 34 mm	left / right

# Product data sheet | Page 3 of 3 GEZE ActiveStop surface-mounted configured \*



\* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.

**GEZE GmbH** | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com 2024-04-21T14:33:10Z