

Product data sheet  
**Levolan 60 glass  
fanlight attachment**



Sliding door fitting for 60 kg glass leaves and fanlight attachment

### AREAS OF APPLICATION

- For design-oriented interior sliding doors for living and office areas
- For all single- and multiple-leaf sliding doors
- Attachment directly to glass
- For attachment on the wall and ceiling (directly and concealed) as well as for glass installation
- Damped on one or both sides with Levolan 60 SoftStop
- Smooth running with Levolan 60 SoftStop makes it particularly well suited for doors in living and office spaces

### PRODUCT FEATURES

- Modular fixed panel option as an "add-on" for the basic hardware
- Up to 60 kg leaf weight and direct attachment to glass walls or fanlight
- With damping on one or both sides for doors with up to 60 kg leaf weight, so that the door is quietly slowed down and moved automatically into the end position
- Small floor and side profiles create a generous clearance gauge for fixed panels and glass sliding doors
- Fixed glass panels can be installed quickly and easily with rubber seals

### TECHNICAL DATA

Productname	Levolan 60 glass fanlight attachment
-------------	--------------------------------------

### PART

#### LSG GLASS / METAL GLUE \*

Glass metal glueing kit for connecting aluminium brackets with glass panes



Designation	Description	Ident-No.
LSG glass / metal glue 50 g *	for up to 30 sliding panels	133039

### LSG GLASS / METAL GLUE \*

Glass metal glueing kit for connecting aluminium brackets with glass panes



Designation	Description	Ident-No.
LSG glass / metal glue 5x1 g *	for up to 5 sliding panels	133056

### LEVOLAN 60 COMPLETE SET

Levolan sliding door fitting for leaf weights up to 60 kg



Designation	Description	Ident-No.	Colour	Leaf width (min.)	Leaf width (max.)
Levolan 60 complete set	For wall installation	147169	Stainless steel optic	400 mm	1240 mm
Levolan 60 complete set	For wall installation	147166	EV1	400 mm	1240 mm
Levolan 60 complete set	For wall installation	147167	Stainless steel optic	400 mm	840 mm
Levolan 60 complete set	For wall installation	147164	EV1	400 mm	840 mm
Levolan 60 complete set	For wall installation	147165	EV1	400 mm	1040 mm
Levolan 60 complete set	For wall installation	147168	Stainless steel optic	400 mm	1040 mm

### ACCESSORIES

#### SPACER PROFILE FOR WALL CLEARANCE LEVOLAN 60 / 120

Spacer profile for wall installation of Levolan 60/120



Designation	Description	Ident-No.	Colour
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	157993	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147571	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147557	EV1
Spacer profile for wall clearance Levolan 60 / 120 *	10 mm additional space, can be stacked up to 20 mm	147559	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147572	Stainless steel optic

# Levolan 60 glass fanlight attachment



Designation	Description	Ident-No.	Colour
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147558	EV1
Spacer profile for wall clearance Levolan 60 / 120	bespoke configuration	147573	
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	157991	EV1
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147560	Stainless steel optic
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147556	EV1
Spacer profile for wall clearance Levolan 60 / 120	10 mm additional space, can be stacked up to 20 mm	147555	EV1

## LEVOLAN SOFTSTOPDUO SET, DAMPED ON BOTH SIDES, UP TO 100 KG

Levolan SoftStopDuo draw-in damping on both sides for leaf weights up to 100 kg



Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)
Levolan SoftStopDuo set, damped on both sides, up to 100 kg	for draw-in damping left & right, consisting of; 1 x double damping unit, 2 x spacers - Levolan 60 and 2 x spacers - Levolan 120 for cover panel bracket, 2 x adjustable triggers, can also be retrofitted - for Levolan 60 minimum leaf width 770 mm, for Levolan 120 minimum leaf width 1010 mm	146402	770 mm	1240 mm

## LEVOLAN 60 SOFTSTOP SET, DAMPED ON ONE SIDE, UP TO 60 KG

Levolan SoftStop draw-in damping on one side left version



Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)
Levolan 60 SoftStop set, damped on one side, up to 60 kg	for draw-in damping left, consisting of: 1 x damping unit, 1 x spacer for cover panel bracket, 1 x trigger, can also be retrofitted - minimum leaf width 570 mm	146370	570 mm	1240 mm

# Levolan 60 glass fanlight attachment



## LEVOLAN 60 SOFTSTOP SET, DAMPED ON ONE SIDE, UP TO 60 KG

Levolan SoftStop draw-in damping on one side right version



Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)
Levolan 60 SoftStop set, damped on one side, up to 60 kg	for draw-in damping right, consisting of: 1 x damping unit, 1 x spacer for cover panel bracket, 1 x trigger, can also be retrofitted - minimum leaf width 570 mm	146401	570 mm	1240 mm

\* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.